



SRNO PN 1011

DHP-100-M Digital Helium Porosimeter (manual)

Portable bench top model that can be used with any type of core holder - manual

ADVANTAGES

- Measures both grain volume using internal matrix cup for samples and directly pore volume using ext. core holder.
- Porosimeter have several reference volumes (V1) that can be combined in order to adjust the ref. volume to achieve optimal calibration results for diff. sample sizes.
- There is also possibility to connect an external tank to increase the ref. volume e.g. for measuring whole core.
- Matrix cups with different internal diameter can be used.
- Pneumatic open/close function for matrix cup for rapid loading and off-loading of samples, gives a high through-put.
- When using external core holder for pore volume measurements, helium is injected from both ends of the sample in order to reduce the time to reach equilibrium.
- The instrument has 2 pcs. in-line temperature sensors with display to monitor the T1 (@V1) and T2 (@V2). It is vital that the temperature at calibration is the same during the measurements, to secure accuracy and repeatability.



SPECIFICATIONS:

Methodology applied:	Boyle's Law @constant temp.
Working Helium Pressure:	0-10 bar (0-145 psi)
Confining Pressure:	Depending on core holder type
Working temperature:	Ambient
Sample diameters (std.):	Ø1.0" - Ø30mm - Ø1.5" - 40mm
Number of matrix billets:	5 pcs. for each sample diameter
Sample length:	0-100 mm (0-4")
Process valves (Helium):	Ball valves and toggle valves
Type of gas required:	Helium and Nitrogen, 10 bar
Type of mounting:	Vacuum expansion directly
Physical size:	500mm 440mm x 400mm
Weight with matrix cup:	29 KG

CERTIFICATES:

Certificate of Conformity/CE mark:	YES
Pressure Leak Test Certificate:	YES
Calibration Certificates Pressure Gauge:	YES
Calibration Certificates Ref. Samples:	YES
Warranty Certificate:	YES

ACCESSORIES:

- Matrix cups and calibration billets in other sizes
- Core Holders of various types and sample sizes
- Kit with 6 pcs. calibration samples with wide range
- Replacement kits with tubing, fittings and valves

Contact Equipment Sales or your local Stratum Reservoir location for further details!

Contact Details – Equipment Sales:
 Stratum Reservoir (Norway) AS
 Visit Address:
 Nikkelveien 15
 N-4313 Sandnes – Norway
 Tel.: +47 51816600

Reg. no.: NO938130027
 Mail Address:
 Fabrikkeveien 37
 N-4066 Stavanger – Norway
 Tel.: +47 51816600

Email Address:
equipmentcontact@stratumreservoir.com
 Website:
www.stratumreservoir.com

