

SRNO PN 1033



STRATUM
RESERVOIR

RES-1150 Hydrostatic/BI-axial Core Holder

Quick-load light weight hydrostatic/BI-axial core holder, Ø1.5" diameter samples

ADVANTAGES

- Light weight Aluminum core holder for multi-purpose measurements in the laboratory such as porosity and permeability, where high through put is required.
- One of the axial end-stems has a piston cylinder that can operate the end-stem at different- or same pressure as the radial sleeve pressure.
- End-stems are electrical insulated to allow electrical properties, such as FRF versus pressure and Resistivity Index at elevated pressures and temperature.
- Core holder can be configured with multiple inlets/outlet.

SPECIFICATIONS:

Working Pressure:	200 bar (2,900 psi) @ room temp.
Test Pressure:	300 bar (4,350 psi) @ Room temp.
Working temperature:	Ambient to +65 °C
Length without valves:	260mm (L=0-70mm samples)
Weight without valves:	3.5 KG (L=0-70mm samples)
Material non-wetted parts:	Aluminum
Material wetted parts:	SS-316L
Insulation material:	Annealed PEEK/POM
Confining Valve:	Autoclave
Process Valves:	Swagelok or similar
O-ring materials:	Viton-75, Viton-90 or Kalrez
Core Sleeve Materials:	FKM (Viton-75, std.) or Nitrile
Core Sleeve Dims. 1.0":	I.D. 36mm x 2,0mm wall (std.)
Type of sample mounting:	Direct vacuum expansion of sleeve



CERTIFICATES:

Certificate of Conformity:	YES
Pressure Test Certificate:	YES
Traceability List:	YES
CE Marked:	YES
Material Certificates:	YES

ACCESSORIES:

Replacement kits with tubing, fittings and valves
Consumables such as rubber sleeves, PEEK and O-rings

Contact Equipment Sales or your local Stratum Reservoir location for further details!

Contact Details – Equipment Sales:
Stratum Reservoir (Norway) AS
Visit Address:
Nikkelveien 15
N-4313 Sandnes – Norway
Tel.: +47 51816600

Reg. no.: NO938130027
Mail Address:
Fabrikkveien 37
N-4066 Stavanger – Norway
Tel.: +47 51816600

Email Address:
equipmentcontact@stratumreservoir.com
Website:
www.stratumreservoir.com

